

DIGITALPRINTER RTF



RTF


 Stampante Digitale RTF

Digital Printer RTF 




La RTF è una stampante roll-to-roll ad alte prestazioni che, grazie ai tavoli di supporto, può essere utilizzata anche come flatbed, permettendo la stampa anche su grandi formati rigidi
 È equipaggiata con testine Ricoh GEN5 e raggiunge velocità di stampa fino a 14 m²/h, con configurazioni colore fino a 8 teste di stampa (CMYK + LC + LM + Bianco + Vernice)
 Dispone di altezza di stampa regolabile fino a 70 mm, assicurando la massima versatilità


La RTF offre grande flessibilità grazie alla possibilità di scegliere tra diverse configurazioni di teste ed è disponibile in due versioni di larghezza di stampa: 1600 mm e 2500 mm




Tre file da 6 colori (Bianco + Colori + Vernice)



Tre file da 5 colori (Bianco + Colori + Doppio Colore)



Quattro file da 6 colori (Bianco + Doppio Colore + Vernice)




Quattro file da 4 colori (Solo Colori)




The RTF is a high-performance roll-to-roll printer that, thanks to its support tables, can also be used as a flatbed, allowing printing on large rigid materials
 It is equipped with Ricoh GEN5 printheads and achieves print speeds of up to 14 m²/h, with colour configurations of up to 8 printheads (CMYK + LC + LM + White + Varnish)
 It has an adjustable print height up to 70 mm, ensuring maximum versatility

The RTF offers great flexibility thanks to the possibility of choosing between different head configuration and is available in two printing widths: 1600 mm and 2500 mm




Three rows of 6 colors (W+C+V)



Three rows of 5 colors (W+C+C)



Four rows of 6 colors (W+C+C+V)



Four rows of 4 colors (All Color)

	RTF
Print Technology	Industrial Piezoelectric Inkjet
Colour Configuration	4 Color/ 6 Color/ White/ Varnish Optional
Print Height	2-70mm Above Media Adjustable
Power	5KW AC220V (±5%); 50HZ/ 60HZ
Humidity	35~80% RH (NO Condensing)
Temperature	25~32° C or more Recommended no Frost
Printing width	1600 mm or 2500 mm (depending on model)



Ser.Tec. Srl

Via Emilio Salgari 14/d - 31056 Roncade (TV) - Italy
 Phone +39 (0)422 798184 - Fax. +39 (0)422 799711
 e-mail: sales@ser-tec.org - Website: ser-tec.org



www.facebook.com/sertecsr



www.instagram.com/sertecgroup

Ser.Tec. reserves the right to make changes in specifications, materials and accessories without notice.
 The result may differ from the information in this brochure.



Scan the QR code and visit our web site!